

**DECLARATION OF PERFORMANCE**  
**No RW-CEE-DoP-0660/CM/20/w1**

- |  |  |
|--|--|
| <p>1. Unique identification code of the product-type:<br/><b>RW-CEE-0660</b></p> <p>2. Intended use/es: <b>Thermal insulation products for buildings (ThiB).</b></p> <p>3. Manufacturer: <b>ROCKWOOL® Polska Sp. z o.o.,<br/>ul. Kwiatowa 14, 66-131 Cigacice.</b></p> | <p>4. System/s of AVCP: <b>System 1 and System 3</b></p> <p>Harmonised standard: <b>EN 13162:2012+A1:2015</b></p> <p>5. Notified body No <b>1390</b></p> <p>6. Declared Performance/s: in the Table 1 and Table 2:</p> |
|--|--|

Table 1

Essential Characteristics	Performance	Declared value / NPD <sup>1)</sup>	Harmonized technical specification
Thermal resistance	Thermal resistance $R_0$ and $d_N$ thermal conductivity $\lambda_D$	see Table 2 0,040 W/mK	EN 13162:2012+A1:2015
	Ti <sup>*)</sup> Thickness	T5	
Reaction to fire	Euroclasses – Reaction to fire (Rf) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (Rf) product <sup>2)</sup>	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance $R_0$ and thermal conductivity $\lambda_D$ (W/mK) <sup>2)</sup>	see Table 2 0,040 W/mK	
	Durability characteristics	NPD	
Compressive strength	Compressive stress CS(10) <sup>*)</sup> , CS(10/Y) <sup>*)</sup> (kPa)	NPD	
	Point load PL(5) <sup>*)</sup> (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR <sup>*)</sup> (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS ( $\leq 1$ kg/m <sup>2</sup> )	NPD	
	Long term water absorption WL(P) ( $\leq 3$ kg/m <sup>2</sup> )	NPD	
Water vapour permeability	Water vapour transmission	NPD	
	Water vapour diffusion resistance factor		
Impact noise transmission index (for floors)	Dynamic stiffness SD <sup>*)</sup>	NPD	
	Thickness, $d_L$	NPD	
	Compressibility c	NPD	
	Air flow resistivity AFr <sup>*)</sup>	NPD	
Acoustic absorption index	Sound absorption AW <sup>*)</sup>	NPD	
Direct airborne sound insulation index	Air flow resistivity AFr <sup>*)</sup>	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

<sup>1)</sup> No performance determined (NPD); <sup>2)</sup> no change with time; <sup>\*)</sup> \*\* indicates relevant class of level or declared value.

Table 2

$d_N$ (mm)	40	80	100	102	103	108	126	129	130	150	180	200	202	230	232	240	-	-	-	-	-	-
$R_0$ (m <sup>2</sup> K/W)	1,00	2,00	2,50	2,55	2,55	2,70	3,15	3,20	3,25	3,75	4,50	5,00	5,05	5,75	5,80	6,00	-	-	-	-	-	-

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Halina Ozon

Cigacice, 2020-07-26

